

CLAIMS

What is claimed is:

1. Device for mixing two pasty substances, in particular a dental impression substance with a catalyst substance, the device comprising
 - a housing (42) comprising an essentially tubular section (44) having two radial inlet openings (68,70) for the two pasty substances at the rear end and an outlet opening (52) for the mixed pasty substances at the front end of the tubular section (44),
 - a driveable mixer shaft (38) extending through the tubular section (44) and rotatably supported in the housing (42),
 - wherein the mixer shaft (38) comprises a plurality of rigid mixer elements (74) protruding from an axis (72) and serving for mixing the two pasty substances during their passage through the tubular section (44) of the housing (42),

characterized in that

 - the mixer shaft (38) comprises at the level of the inlet openings (68,70) at least one deflection element (80) for promoting the transport in axial direction of the pasty substances fed through the inlet openings (68,70) to the tubular section (44) of the housing (42), wherein the at least one deflection element (80) comprises a deflection surface (82) extending about the axis (72) and at an inclination to a radial plane of the axis (72).
2. Device according to claim 1, characterized in that the at least one deflection element (80) is designed as a wedge.
3. Device according to claim 1 or 2, characterized in that two deflection elements (80) are provided which are arranged diametrically opposite each other about the axis (72).

T09410-20340000

4. Device according to one of claims 1 to 3, characterized in that the two deflection elements (80) extend over an angular range of 90° to 180° .
5. Device according to one of claims 1 to 4, characterized in that the at least one deflection element (80) comprises a deflection surface (82) helically extending about the axis (72).
6. Device according to one of claims 1 to 5, characterized in that the housing (42) comprises at its rear end (48) an insertion part (62) oriented transversally to the axis (72), the insertion part (62) comprising an outer surface forming the rear end (48) of the housing (42) and an inner surface facing the tubular section (44) of the housing (42), the inner surface being provided with a cylindrical deepened reception portion (69) for the section of the mixer shaft (38) carrying the at least one deflection element (80), and that the outer surface of the insertion part (62) comprises two inlet stubs (54,56) from which two ducts (64,66) extend through the insertion part (62), in which ducts (64,66) end radial openings of the cylindrical deepened reception portion (69) forming the inlet openings (68,70).
7. Device according to one of claims 1 to 6, characterized in that an identical number of mixer elements (74) within a plurality of radial planes protrude from the axis (72) and extend up to near the inner surface (76) of the tubular section (44) of the housing (42).
8. Device according to claim 7, characterized in that within a number of radial planes equal to the number of mixer elements (74) per radial plane two mixer elements (74) respectively adjacent to each other in circumferential direction are connected with each other via a portion (78,78') extending in circumferential direction, and that these pairs of mixer elements (74) connected with each other are staggered from radial plane to radial plane in circumferential direction.

- Add
A2

[Handwritten signature]